

INTENSIFIA™

DEEP ENHANCEMENT & STAIN PROTECTION

Deep, long lasting color enhancement and premium stain protection for porous surfaces, including natural stone, brick, paving and masonry



- Provides deep color enhancement
- Premium oil and water based stain protection**
- Easy to apply
- Breathable: water vapor permeates freely, avoiding moisture build-up inside the material
- Retains wet slip resistance of porous flooring material
- Suitable for indoor, outdoor, residential and commercial use
- 5 year warranty*

INTENSIFIA™ WILL PROTECT:

- | | |
|-------------------|--------------------|
| ■ Basalt | ■ Marble |
| ■ Brick | ■ Quarry tiles |
| ■ Cement pavers | ■ Saltillo tiles |
| ■ Clay pavers | ■ Sandstone |
| ■ Concrete | ■ Slate |
| ■ Encaustic tiles | ■ Terracotta tiles |
| ■ Granite | ■ Terrazzo |
| ■ Grout | ■ Travertine |
| ■ Limestone | |



BASIC SEALING GUIDE

BEFORE SEALING:

- Surfaces must be thoroughly clean and dry before applying a sealer. Once sealed, the surface becomes water repellent, making it tough to remove existing stains.

ALL YOU WILL NEED:

- INTENSIFIA™
- Low pressure hand spray/lamb's wool applicator/brush
- Sufficient white absorbent cloths/towels
- Safety gear (gloves, protective eyewear, mask or chemical respirator if in a confined space)

SEALING IN 5 EASY STEPS: (Refer to the back of the label for more information)



- 1. TEST:** Test product on a small area of the surface, wait 24 hours, and ensure you are satisfied with the results.



- 4. REMOVE EXCESS:** Before the first coat dries, thoroughly polish off all residue with clean, dry cotton cloths / towels, then let the product cure for at least an hour.



- 2. CLEAN:** Make sure the area to be treated is clean, dry and free of residues or topical coatings.



- 5. SECOND COAT:** Repeat steps 3 and 4. A third coat may be required for premium stain protection on extremely porous surfaces. Ensure that all residue are thoroughly polished off.



- 3. FIRST COAT:** Generously saturate the surface with INTENSIFIA™ using a lamb's wool applicator / brush / pump spray. Leave to penetrate for at least 30 minutes.

Note: Surface can be walked on 2-3 hours after application. Do not get the surface wet for at least 8-10 hrs.

MAINTAINING YOUR SEALED SURFACE:

Dry-Treat has developed specialist cleaners under the HANAFINN™ brand to clean and maintain your natural stone surface.



**HANAFINN
Oxy-Klenza™**
for outdoor surfaces
and stain removal



**HANAFINN
Rejuvenata™ Active**
for indoor surfaces
and stain removal



**HANAFINN
Rejuvenata™ Spray**
for daily
countertop cleaning



**HANAFINN
Eff-Erayza™**
for removing of efflorescence,
rust marks and grout haze

For advanced application guide and complete guide on how to maintain your sealed surface, visit:

www.drytreat.com/quickdocs.html

Dry-Treat
Andover, MA, USA
Ph: 1866 667 5119

Dry-Treat
St Leonards, NSW, AU
Ph: 1800 675 119

Dry-Treat Ltd
United Kingdom
Ph: 0800 096 4760

www.drytreat.com

info@drytreat.com